



ZEOTEC

ZEOTEC 1900L

- GENERAL DESCRIPTION:** ZEOTEC 1900L is a catalyzed liquid oxygen removal agent
- RECOMMENDED USE:** ZEOTEC 1900L is recommended for removing dissolved oxygen from closed hot water heating and chilled water loops to prevent corrosion problems.
The recommended injection point is into the water loop as low in the system as possible but still convenient.
- TECHNICAL SPECIFICATIONS:** Colour..... Straw Coloured Liquid
Specific Gravity..... 1.05
Pounds/Imperial Gallon..... 10.5
Freeze Point..... 16 Degrees F
pH As Supplied..... 8.3
Viscosity..... 5.0 cps @ 25 Degrees C
- HANDLING & STORAGE:** ZEOTEC 1900L is an industrial chemical and all precautions taken in handling these chemicals should be observed. The eyes should be protected by splash proof equipment and gloves should be worn. ZEOTEC 1900L is not especially toxic and can be removed from contaminated clothing or eye or skin contact by flushing with plenty of water. If any eye or skin contact, after flushing with water, seek medical attention.
- Avoid freezing.
- DOSAGE & CONTROL:** The required control range is 50 to 100 ppm S03 residual in the boiler water at all times.
- PACKAGING:** ZEOTEC 1900L is available in 20 L / 5 USG plastic pails
- PRICING:** Contact Zeotec Limited

WATER MANAGEMENT CHEMICALS * EQUIPMENT * LABORATORY SERVICES

Zeotec Limited
9643 62 Ave NW Edmonton AB T6E 0E1
P: 780.434.5810 | TF: 1.888.434.5810
info@zeotec.com