

## ZEOTEC DISPERSEX

GENERAL DESCRIPTION: ZEOTEC DISPERSEX is a stabilized, liquid, boiler water

treatment formulation of organic and inorganic alkaline ingredients including oxygen scavenger for corrosion control.

RECOMMENDED USE: ZEOTEC DISPERSEX is designed to remove and prevent scale

and corrosion in operating boilers by sequestration, precipitate

conditioning and oxygen scavenging.

TECHNICAL SPECIFICATIONS: Specific Gravity................... 1.09

Flash Point.....None

pH of 1% Solution...... 11

Solubility...... Miscible in water of

all proportions

Temperature Stability.....+400 Degrees F

(200 Degrees C)

HANDLING & STORAGE: Handle ZEOTEC DISPERSEX like any other mild alkali. Do

not take internally. Avoid eye and skin contact. If eye or skin contact, immediately flush with plenty of water and seek medical

attention.

Avoid freezing.

DOSAGE & CONTROL: ZEOTEC DISPERSEX should be added as a 5% to 15%

solution in good quality water to the boiler feedwater storage tank.

Keep boiler water pH in the range of 10.0 to 11.5 and/or boiler

water conductivity at 2000 to 3000 microSiemens.

PACKAGING: ZEOTEC DISPERSEX is available in 5 USG plastic pails.

PRICING: Please contact Zeotec Ltd for pricing.

WATER MANAGEMENT CHEMICALS \* EQUIPMENT \* LABORATORY SERVICES