



ZEOTEC

ZEOTEC 5900

- GENERAL DESCRIPTION:** ZEOTEC 5900 is a liquid corrosion inhibitor containing nitrite, metaborate, copper corrosion inhibitors and pH buffers.
- RECOMMENDED USE:** ZEOTEC 5900 is designed to control corrosion and scale in closed circulating, chilled and hot water heating systems.
- TECHNICAL SPECIFICATIONS:** Colour..... Clear, Slightly Yellow
Specific Gravity..... 1.18
pH of 1% Solution..... 11.0
Solubility..... All proportions in water,
15% maximum in ethylene glycol
- HANDLING & STORAGE:** Do not take internally. Avoid eye and skin contact; wear goggles and gloves. If eye or skin contact, flush with plenty of water and seek medical attention.
- Avoid freezing.
- DOSAGE & CONTROL:** Use minimum of 8 L per 1,000 L (1%) of system capacity in untreated systems. After startup, dosage is 6 L per 1,000L (0.6%) of system capacity to maintain a control dosage of 500 to 1000 ppm of NO₂ (nitrite).
- PACKAGING:** ZEOTEC 5900 is available in 5 USG plastic pails.
- PRICING:** Contact Zeotec Limited

WATER MANAGEMENT CHEMICALS * EQUIPMENT * LABORATORY SERVICES